



**Omniseal Solutions**  
SAINT-GOBAIN

# Life Science Industry Handbook



Beyond the boundaries of  
**POSSIBLE**





## Life Science Sealing & Friction Control Materials

Code No.	Base Material	Color	Temperature Range	
			°F	°C
High-Performance Polymer Sealing Materials				
A01	PTFE	White	-450°F to +500°F	-268°C to +260°C
A02	PTFE	White	-450°F to +600°F	-268°C to +316°C
A06	PCTFE	White	-435°F to +400°F	-259°C to +204°C
A12	PTFE	Dull Gold	-450°F to +550°F	-268°C to +288°C
A17	UHMW	White	-450°F to +180°F	-268°C to +82°C
A20	FEP	Clear	-320°F to +400°F	-196°C to +204°C
A22	PEEK	Tan	-100°F to +600°F	-73°C to +316°C
A23	UHMWPE	Clear	-250°F to +200°F	-156°C to +93°C
A29	PTFE	Black	-400°F to +550°F	-240°C to +288°C
A40	PTFE	Beige	-400°F to +550°F	-240°C to +288°C
A45	PTFE	Brown	-400°F to +550°F	-240°C to +288°C
A46	PTFE	White	-400°F to +550°F	-240°C to +288°C
A47	PTFE	White	-400°F to +550°F	-240°C to +288°C
A66	PFA	Clear	-320°F to +500°F	-196°C to +260°C
A79	PTFE	White	-400°F to +550°F	-240°C to +288°C
Rulon® Bearing, Sealing and Structural Materials				
Rulon® J	PTFE	Dull Gold	-450°F to +550°F	-268°C to +288°C
Rulon® 123	PTFE	Black	-400°F to +550°F	-240°C to +288°C
Rulon® 1337	PTFE	Beige	-400°F to +550°F	-240°C to +288°C
Rulon® 641	PTFE	White	-400°F to +550°F	-240°C to +288°C
Rulon® 1439	PTFE	White	-400°F to +550°F	-240°C to +288°C

## Extend Your Performance & Life Requirements

- Precision custom sealing
- Minimally invasive designs
- Extend maintenance cycles
- Protect electronics
- Validation & simulation testing

## Tailor-Made Designs, Materials & Manufacturing

- Wear & friction control
- Lightweight and self-lubricious options
- Sterilization & chemical resistance
- Cost-efficient manufacturing options



## GOING BEYOND WITH SEALING & MATERIAL SOLUTIONS




### Rulon® Polymer Cup Seals

Portable oxygen concentrator  
Nebulizer



### Omniseal® Spring-Energized Seals

Surgical tools  
HPLC/UHPLC



### Rulon® Wear Components

Surgical tools  
In Vitro Diagnostics



### Meldin® Bearings

Surgical tools  
Endodontics (obtrusion)



### Omniseal® Lip Seals

Pharmaceutical Mixer  
Home Medical Equipment – Respiratory  
Surgical Tools

## Proven in the Past...

For more than 50 years, Omniseal Solutions has been a trusted manufacturing partner to the medical, surgical, dental, analytical and pharmaceutical markets.

Our commitment to innovation and sustainable solutions drive our ongoing effort to better serve our customers.

... Prepared for the Future

## Purity and Cleanliness

From material selection to clean room operations, Omniseal Solutions offers the technology and infrastructure to support today's Life Science customer. Our extensive material catalog includes 22 materials that are FDA compliant or USP Class VI certified, such as PEEK, PTFE, PCTFE, UHMW-PE and PFA based compounds. Our Garden Grove, California facility has Class 100 and 10K clean rooms to control contamination.

### KEY APPLICATIONS

Analytical equipment	In Vitro diagnostic equipment
Pharmaceutical processing	Surgical and dental tools

## Critical Sealing

Our seals are designed to provide the precise level of sealing required by the application. In the Life Science industry, proper sealing can protect integral components and result in substantial cost savings for the end user by extending maintenance cycles and increasing the overall life of the application.

### KEY APPLICATIONS

Surgical robotics & in vitro diagnostics	Analytical equipment
	Home medical equipment, oxygen concentrator

## Friction Control

Omniseal Solutions offers two material grades, Rulon® and Meldin®, that address the need for structural components and bearings in dynamic applications. These material grades have been formulated for low wear and thermal stability. When it comes to friction and sealing, our Omniseal® spring-energized and lip seals can be optimized for low and high PV applications, respectively.

### KEY APPLICATIONS

Home medical equipment – respiratory	Dental drills
Surgical tools	Surgical robotics & in vitro diagnostics

## Chemical Compatibility

Many applications in the Life Science industry deal with extreme chemical environments requiring chemical sterilization and cleaning in place (CIP) techniques. Whether the media is alkaline, acidic or a unique solvent, Omniseal Solutions offers a material compound to meet your specific chemical needs as well as providing hundreds of unique compounds, including 22 that are FDA or USP Class VI compliant.

### KEY APPLICATIONS

Pharmaceutical processing	Analytical equipment
	Surgical tools





# CRITICAL PARTS PROTECTING CORE LIFE SCIENCE SYSTEMS

Omniseal Solutions™ has a rich history servicing the unique challenges of the Life Science market. With a focus on customer collaboration and new product development, we provide the support and technical expertise to meet just about any challenge.


## Our Core Competencies:

- Design engineering
- Precision fabrication
- Material formulation
- Customer collaboration
- Purity and cleanliness
- Critical sealing
- Friction control
- Weight reduction
- Lower cost of ownership for end users
- Custom Shapes and Sizes (Miniaturization)



Solutions		Main Features
OMNISEAL® POLYMERS	High-Performance Spring-Energized Seals	<ul style="list-style-type: none"><li>• Temperatures from -210°C to +316°C (-346°F to +600°F)</li><li>• Pressure: Vacuum up to 3,448 bar (50,000 psi)</li><li>• Low and controlled friction</li><li>• Broad chemical resistance</li></ul>
	High-Performance PTFE Rotary Shaft Seals	
RULON® FLUOROPOLYMERS	High-Performance Fluoropolymer Compounds	<ul style="list-style-type: none"><li>• Temperatures from -268°C to +316°C (-450°F to +600°F)</li><li>• Low friction, high wear life and broad chemical resistance</li></ul>
MELDIN® POLYIMIDES	High-Performance Thermoset Polyimide Materials	<ul style="list-style-type: none"><li>• Temperatures from cryogenic through +316°C (+600°F), intermittently up to +482°C (+900°F)</li><li>• Superior strength and rigidity combined with self-lubrication properties</li></ul>
HYCOMP™ COMPOSITES	High-Performance Composite Components	<ul style="list-style-type: none"><li>• High Temperature capabilities up to +350°C (+662°F)</li><li>• Very low coefficient of thermal expansion</li><li>• Good thermal oxidative stability</li><li>• Lightweight &amp; high wear resistance</li></ul>

# ONE GLOBAL TEAM... A DEDICATED CUSTOMER FOCUS



## GLOBAL & LOCAL PRESENCE

With 17 manufacturing facilities in 10 different countries, Omniseal Solutions™ is a diverse group that is committed to being customer centric.

### Contact our team of experts for more information. We have local resources to support you!

- **Americas:** Garden Grove, CA, USA; Bristol, RI, USA; Orange, CT, USA; Cleveland, OH, USA; Northboro, MA; Saltillo, MX
- **Europe:** Kontich, Belgium; Mechelen, Belgium; Vimercate, IT; La Rioja, Spain; Kolo, Poland; Willich, Germany
- **Asia:** Shanghai, China; Bangalore & Chennai, India; Suwa & Tokyo, Japan; Seoul & Incheon, South Korea; Taipei, Taiwan

[help@omniseal-solutions.com](mailto:help@omniseal-solutions.com)

[www.omniseal-solutions.com](http://www.omniseal-solutions.com)

Omniseal®, Rulon®, Meldin®, and Hycomp™ are registered trademarks of Saint-Gobain Performance Plastics Corporation.

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

NOTE: Omniseal Solution™ and Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

BST-4186-0823

©2023 Omniseal Solutions™



**Omniseal Solutions**  
SAINT-GOBAIN

